# To Crop, Or Not to Crop: Compiling Online Media Galleries

Thomas Steiner Google Germany GmbH ABC-Str. 19 20354 Hamburg, Germany tomac@google.com

## ABSTRACT

We have developed an application for the automatic generation of media galleries that visually and audibly summarize events based on media items like videos and photos from multiple social networks. Further, we have evaluated different media gallery styles with online surveys and examined their pros and cons. Besides the survey results, our contribution is also the application itself, where media galleries of different styles can be created on-the-fly. A demo is available at http://social-media-illustrator.herokuapp.com/.

## **Categories and Subject Descriptors**

H.3.3 [Information Search and Retrieval]: Clustering

# **General Terms**

Algorithms

#### Keywords

Media Galleries, Event Summarization, Social Networks

#### **1. INTRODUCTION**

Media galleries (see Figure 1 for examples) help users consume larger, however not overwhelmingly huge, amounts of media items in an ideally pleasing and aesthetic way. These media items may, or, more commonly, may not be ordered, besides an intrinsic chronologic order. In the context of our work on summarizing events based on microposts and media items stemming from multiple social networks, we have created methods to first *extract* event-related media items from multiple social networks, second, to *deduplicate* nearand exact-duplicate media items, third, to *cluster* them by visual similarity, and finally, to rank the resulting media item clusters according to well-defined ranking criteria. In this paper, we treat the challenge of *compiling* ranked media item clusters in media galleries in ways such that the ranking-implied order is (loosely) respected. Previously, we have defined [3] aesthetic principles for automatic media gallery layout, which we now apply to media gallery styles. The task of media gallery compilation is different from the widely researched task of photo book generation, as media galleries can contain both, photos and videos. Different types of media gallery layouts are possible, two of which we have implemented and evaluated via two different user studies. One with, and one without detailed user comments.

Copyright is held by the author/owner(s).

Christopher Chedeau Facebook, Inc. 1601 Willow Road Menlo Park, CA, 94025, USA vjeux@fb.com

## 2. MEDIA GALLERY STYLES

Media galleries—in contrast to free-form digital media collages-necessarily display media items in a grid-like way. The crucial question is thus, whether the media items' aspect ratios should be respected, or whether they should be cropped to square, or other aspect ratios (e.g., 4:3 or 16:9). Respecting the aspect ratio has the advantage that media items do not need to be potentially lossily cropped, however, due to the unpredictable media item formats, compiling media galleries that do not look frayed is harder. The advantage of cropping is that media gallery layout is easier, as the media item formats are predictably the same, at the cost of having to decide where to crop. Different algorithms (e.q., [4]) beyond this paper's scope exist to aid this decision. A media gallery is called *balanced*, if its shape is rectangular, hole-free if there are no gaps from missing media items, and order-respecting, if media items appear in insertion order.

## 2.1 Non-Order-Respecting Styles

An interesting technique for arranging media items is dividing. Every media item with an aspect ratio of  $\sqrt{2}$  can be divided into two media items with the same aspect ratio.<sup>1</sup> This works for portrait and landscape orientations, however, is not order-respecting. Two other non-order-respecting techniques are (i), working with pre-defined placeholder patterns (small and big squares, portrait and landscape rectangles) and then filling the placeholder shapes with media items,<sup>2</sup> or (ii), working with columns of pre-defined widths and then iteratively inserting in the smallest column.<sup>3</sup> As outlined in Section 1, we need (loosely) order-respecting media galleries.

#### 2.2 Strict Order, Equal Size (SOES)

A media gallery style that we call *Strict Order, Equal Size* (SOES), which strictly respects the ranking-implied order is presented in [2]. Examples can be seen in Subfigure 1a and Subfigure 1c. The algorithm works by resizing all media items in a row to the same height and adjusting the widths in a way that the aspect ratios are maintained. A row is filled until a maximum row height is reached, then a new row (with potentially different height) starts, *etc.* This media gallery style is order-respecting, hole-free, and can be balanced by adjusting the number of media items in +1 steps.

algorithm-500px.html, as of 03/26/2013

WWW 2013 Companion, May 13–17, 2013, Rio de Janeiro, Brazil. ACM 978–1–4503–2038–2/13/05.

 $<sup>^1\</sup>rm http://blog.vjeux.com/2012/image/image-layout-algorithm-lightbox-android.html, as of <math display="inline">03/26/2013$   $^2\rm http://blog.vjeux.com/2012/image/image-layout-$ 

 $<sup>^{3}\</sup>mbox{http://blog.vjeux.com/2012/image/image-layout-algorithm-lightbox.html, as of <math display="inline">03/26/2013$ 



Figure 1: Two different kinds of media galleries visualizing a gathering at Times Square, New York on February 8, 2013

# 2.3 Loose Order, Varying Size (LOVS)

Examples of a media gallery style that we call *Loose Or*der, Varying Size (LOVS) can be seen in Subfigure 1b and Subfigure 1d, with the details explained in [1]. The algorithm works by cropping all images to a square aspect ratio, which allows for organizing media items such that one big square always contains two horizontal blocks, each with two pairs of small squares. The media gallery is then formed by iteratively filling big or small squares until a square is full, and then adding it to the smallest column. This media gallery style allows any media item to become big, while still being loosely order-respecting and always hole-free. Balancing the gallery is slightly harder, as in the worst case up to  $(bigBlocksPerRow - 1) \times 2$  media items may be required.

#### 3. DISCUSSION

The main motivation for the *Loose Order, Varying Size* style is that certain media items can be featured more prominently by making them big, while still loosely respecting the ranking-implied order. Examples of to-be-featured media items can be videos, media items with faces, media items available in High-Density quality, or media items with interesting details [4]. Users may want to decide what media items to feature, albeit we aim for an automatized solution.

#### 4. PRELIMINARY EVALUATION

Evaluating subjective data like *the* correct presentation form for a set of media items is a challenging task. For different users, there may be different optimal settings. A common subjective evaluation technique is the Mean Opinion Score (MOS), used for decades in telephony networks to obtain the human user's view of the quality of a network.<sup>4</sup> Recently, MOS has also found wider usage in the multimedia community. Therefore, a set of standard subjective tests are conducted, where users rate the perceived quality of test samples with scores from 1 (worst) to 5 (best). The actual MOS is then the arithmetic mean of all individual scores.

We have conducted two types of surveys. Survey A via multiple social networks, where we simply asked people to "Like" and/or comment on their favorite style of media gallery, and Survey B via email to a company-internal "miscellaneous" mailing list, where we asked people to rate media galleries via MOS, with optional comments. Survey A and Survey B used different media items in the media galleries, as to have some measure in how far content has an impact. For Survey A on the social networks Twitter, Facebook, and Google+, we had overall 16 participants (7 female, 8 male, 1 unknown). 7 users liked SOES more, whereas 9 users liked LOVS more. Interestingly, no user commented on why they liked SOES more. Users who commented on why they liked LOVS more mentioned they liked the additional structure and tidiness, the fact that some media items were bigger, the fact that it was easier to identify individual media items, and the fact that important media items were highlighted.

For Survey B via email with MOS ratings, we had 19 participants (6 female, 13 male). The majority of users who liked LOVS more mentioned that the different sizes gave the eye focal points and orientation, whereas one user explicitly disliked this guidance. Users liked the harmony and the structure. Two users mentioned that small media items were proportionally too small. Regarding *SOES*, users felt overloaded and did not know where to start. Some users said the layout was boring and that, while they liked the outer framing, they were confused by the irregular inner grid. The MOS for *SOES* was 2.39 (variance 0.68), the MOS for *LOVS* was 4.17 (variance 0.47). The data of Survey B is available.<sup>5</sup>

## 5. CONCLUSIONS AND FUTURE WORK

We have created an application that auto-generates two media gallery styles, SOES and LOVS, and evaluated users' perceived quality with two separate surveys. While the data is not significant, the trend is that users seem to prefer LOVS. Future work will be on evaluating more media gallery styles. Concluding, we have learned that eyes need focal points to spot the needles in the media gallery haystack.

## 6. **REFERENCES**

- C. Chedeau. Image Layout Algorithm Facebook, Aug. 2012. http://blog.vjeux.com/2012/image/imagelayout-algorithm-facebook.html, as of 02/22/2013.
- [2] C. Chedeau. Image Layout Algorithm Google+, July 2012. http://blog.vjeux.com/2012/image/imagelayout-algorithm-google.html, as of 02/22/2013.
- [3] T. Steiner, R. Verborgh, J. Gabarro, and R. Van de Walle. Defining Aesthetic Principles for Automatic Media Gallery Layout for Visual and Audial Event Summarization based on Social Networks. In *Quality of Multimedia Experience (QoMEX), 2012 Fourth International Workshop on*, pages 27–28, July 2012.
- [4] B. Suh, H. Ling, B. B. Bederson, and D. W. Jacobs. Automatic Thumbnail Cropping and its Effectiveness. In Proceedings of the 16th Annual ACM Symposium on User Interface Software and Technology, 2003.

 $<sup>^{4} \</sup>rm http://www.itu.int/rec/T-REC-P.800-199608-I/en, as of <math display="inline">03/26/2013$ 

 $<sup>^5</sup>$ http://bit.ly/media-gallery-survey, as of 03/26/2013